

ISR 2022-2023 Rules with the following exceptions:

All Classes:

Sled must have a minimum ride height of three (3) inches measured at the lowest point of the bulkhead/skid plate. Measurement points to be centered directly in front of the track drive area, (using the spindle centers to determine center point of bulkhead) and must retain 2 inches of remaining compression travel with driver on snowmobile.

Stock

Engine

15 – Commercially produced, unmodified, aftermarket exhaust silencers allowed on naturally aspirated 2-stroke models. Turbocharged 2 stroke and all four stroke sleds must use unaltered original equipment muffler.

16 – Any stock qualified sled with a factory equipped turbo charger will compete in the open stock class. (ie 850 turbos from Polaris or BRP, Arctic Cat 9000/Thundercat, Yamaha Sidewinder)

Track & Traction

Section to read:

1 – No cutting, trimming, or shaving of the track or rubber studs/snow lugs allowed. The track must be used as produced by the molder of the track. No traction products allowed. The track may not be reversed. Exceptions may be made for safety reasons to allow professionally narrowed tracks to the original OE width for a sled when replacement tracks are not available in the original width.

All other points in Track & Traction deleted.

Improved Stock

Track Suspension:

6 – (Deleted)

Track & Traction

4 – (Deleted)

5 – (Deleted)

6 – No traction products allowed.

Frame & Body

2 – (Deleted)

Improved Stock 1000 and Open

1 - See SSRA Weight Reference Chart for sled/driver minimum weights.

2 – (Deleted)

Engine

13 – (Deleted)

15 – Improved Stock Open – Factory turbo-charged engines must use OE turbocharger.

Pro Stock

General: Snowmobile must resemble a stock model and profile. Minimum handlebar height 30” inches from ground to center of tube.

Engine

8 - Aftermarket cylinders for the brand are allowed.

18 – Exception: Pro-stock Open

Ski Suspension & Steering

1 – (Addition) A-arm front suspensions may not be changed to single A-arm design. Must retain OE configuration.